Lincat frifri



CO223T - Lincat Convector Touch Electric Counter-top Convection Oven - W 810 mm - D 850 mm - 3.0 kW Able to roast, braise, bake and reheat, a C0223T Convector convection oven is a powerful addition to any commercial kitchen.

- ⊘ 2 x GN1/1 capacity
- Touchscreen control with easy-to-use icon-driven menu selections
- Easy-view traffic light status see the status of the oven at a glance, even in the noisiest kitchens
- Space for 24 programs with up to four stages, which can be adjusted individually
- Up to four-stage phased cooking for perfect results - set temperature, time, fan speed and humidity injection for each stage
- Even heat distribution thanks to electronically controlled two-speed, bi-directional fan
- Five levels of humidity injection
- Nine-hour on-screen timer, with electronic buzzer, and flashing oven lamps to indicate that cycle has finished

Specifications

Summary

Brand Range Series Power Type Unit Type Available in UK Only UK Warranty Export Warranty GTIN

Lincat Convector Touch Electric Counter-top No 2 Years Parts and Labour Warranty Contact your local dealer 5056105118275

Power and Performance

Total Power kW Temperature Range °C IP Rating Controls Position Temperature Control Timer Range mins Oven Rating kW

3.0
30-260
IP23
Right hand side
Electronic
1-540
2.8

Lincat frifri

Key Specifications

.			
Stackable	Yes (with optional kit)	Gastronorm Capacity	2 x GN1/1
Feet Height/Type	55mm/adjustable	Euronorm Capacity	2 x 600 mm x 400 mm
Continuous Plug-In Door Seal	Yes	Shelf Spacing mm	110
Removable Inner Door Glass	Yes	Sheet Pan Capacity	2 x 660 mm x 460 mm
Handle Type	Grab	Capacity Litres	96.0
Vented Door	Yes		
Reversible Door	No		
Door Type	Drop down		
Number of Cooking Phases	4		
Phased Cooking	Yes		
Shelf Timer(s) (Number)	Yes(4)		
Grill Element/Mode	No		
Core Temp Probe	No		
Steam Injection	Yes		
Fan(s) Speed	2		
Fan(s) Type	Bi-Directional		
Number of Fan(s)	1		
Euronorm Compatible	Yes		
Sheet Pan Compatible	Yes		
Removeable Shelf Guides	Yes		
Manual Mode	Yes		
Programmable	Yes		
Number of Programs	24(4 stages)		
Timer Type	Touchscreen		
Display Type	Touchscreen		
Number of Shelves included	2		
Number of Shelf Positions	2		
Type of Lighting	Halogen Bulb		
Construction/Finish	304 S/S cavity		
GN Compatible	Yes		
Weights and Dimensions		Supply Connections	

Capacity

Weights and Dimensions

Unit Height (External) mm	645	Requires Installation	No
Unit Width (External) mm	810	Requires Electrical Supply	Yes
Unit Depth (External) mm	850	UK 3 Pin Plug	Yes
Height (Internal) mm	308	Requires Hardwiring	No
Width (Internal) mm	690	Electrical Supply Rating Watts	3,000
Depth (Internal) mm	470	Single Phase Amps	13.0
Shelf Dimensions Width mm	660	Single Phase Voltage	230
Shelf Dimensions Depth mm	425	Water Connection Pressure Bar	2.0-6.0
Net Weight Kg	80	Drain Connection	No
		Water Connection	3/4" BSPT
		USB Port	Yes


Shipping


Packed Weight Kg	92.1
Packed Height cm	81.5
Packed Width cm	88
Packed Depth cm	100

Available Accessories				
ACIK04	NULL			
CO200/FS	Lincat Convector Floor Stand for C0223M/C0223T/C0235M/C0235T Convection Ovens - with 4 Runners - W 810 mm			
CO200/LFSK	Lincat Convector Low Floor Stand and Stacking Kit for CO223M/CO223T/CO235M/CO235T Convection Ovens - with 1 Runner - W 810 mm			



Technical Picture






Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk



Lincat fift

Lincat Limited

Whisby Road, Lincoln, LN6 30Z,

United Kingdom

Company No: 2175448

A member company of



Export Customers

Tel: +44 1522 503250 Email: export@lincat.co.uk

Opening Hours

Monday – Friday: 8.30am – 5pm