Lincat frifri



CO223M - Lincat Convector Manual+ Electric Counter-top Convection Oven - W 810 mm - D 850 mm - 3.0 kW

- 2 x GN1/1 capacity
- Easy-to-use knob-driven control, and electronic fan control
- Mechanical temperature control from 60° to 260° C
- Even heat distribution thanks to electronically controlled two-speed, bi-directional fan

Able to roast, braise, bake and reheat, a C0223M Convector convection oven is a powerful addition to any commercial kitchen.

- Two fan speeds standard for general use and slow for delicate items
- 120 minute count down timer with electronicallycontrolled buzzer
- Oven lamps flash when cook cycle has finished see when your food is done even in the busiest kitchen

Specifications

Summary

Brand Range Series Power Type Unit Type Available in UK Only UK Warranty Export Warranty GTIN Lincat Convector Manual+ Electric Counter-top No 2 Years Parts and Labour Warranty Contact your local dealer 5056105118268

Power and Performance

Total Power kW Temperature Range °C IP Rating Controls Position Temperature Control Timer Range mins Oven Rating kW 3.0
60-260
IP23
Right hand side
Mechanical
1-120
2.8

Lincat frifri

Key Specifications

Stackable	Yes (with optional kit)
Feet Height/Type	55mm/adjustable
Continuous Plug-In Door Seal	Yes
Removable Inner Door Glass	Yes
Handle Type	Grab
Vented Door	Yes
Reversible Door	No
Door Type	Drop down
Phased Cooking	No
Shelf Timer(s) (Number)	No
Grill Element/Mode	No
Core Temp Probe	No
Steam Injection	No
Fan(s) Speed	2
Fan(s) Type	Bi-Directional
Number of Fan(s)	1
Euronorm Compatible	Yes
Sheet Pan Compatible	Yes
Removeable Shelf Guides	Yes
Manual Mode	Yes
Programmable	No
Timer Type	Mechanical
Number of Shelves included	2
Number of Shelf Positions	2
Type of Lighting	Halogen Bulb
Construction/Finish	430 S/S cavity
GN Compatible	Yes

Capacity

Gastronorm Capacity Euronorm Capacity Shelf Spacing mm Sheet Pan Capacity Capacity Litres 2 x GN1/1 2 x 600 mm x 400 mm 110 2 x 660 mm x 460 mm 96.0

Weights and Dimensions		Supply Connections
Unit Height (External) mm	645	Requires Installation No
Unit Width (External) mm	810	Requires Electrical Supply Yes
Unit Depth (External) mm	850	UK 3 Pin Plug Yes
Height (Internal) mm	308	Requires Hardwiring No
Width (Internal) mm	690	Electrical Supply Rating Watts 3,000
Depth (Internal) mm	470	Single Phase Amps 13.0
Shelf Dimensions Width mm	660	Single Phase Voltage 230
Shelf Dimensions Depth mm	425	USB Port No
Net Weight Kg	78.9	


Shipping


Packed Weight Kg	91
Packed Height cm	81.5
Packed Width cm	88
Packed Depth cm	100

Available Accessories	
CO200/FS	Lincat Convector Floor Stand for CO223M/CO223T/CO235M/CO235T Convection Ovens - with 4 Runners - W 810 mm
CO200/LFSK	Lincat Convector Low Floor Stand and Stacking Kit for CO223M/CO223T/CO235M/CO235T Convection Ovens - with 1 Runner - W 810 mm

Technical Picture








Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk



lincat fift

Lincat Limited

Whisby Road, Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of



Export Customers

Tel: +44 1522 503250 Email: export@lincat.co.uk

Opening Hours

Monday – Friday: 8.30am – 5pm